



**PATENT**  
**5659-08100**  
**TH2006**

CERTIFICATE OF EXPRESS MAIL  
UNDER 37 C.F.R. §1.10

"Express Mail" mailing label number: EL822013524US  
DATE OF DEPOSIT: April 24, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. §1.10 on the date indicated above and is addressed to:

Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

\_\_\_\_\_  
Brit Baker

**IN SITU THERMAL PROCESSING OF A HYDROCARBON CONTAINING  
FORMATION USING PRESSURE AND/OR TEMPERATURE CONTROL**

By:

George L. Stegemeier

Harold J. Vinegar

Scott L. Wellington

Eric P. de Rouffignac

John M. Karanikas

Ilya E. Berchenko

Etuan Zhang

Gordon T. Shahin, Jr.

Thomas D. Fowler

Robert C. Ryan

*In The Specification:*

Listed below is a clean copy of amended paragraphs of the Specification. A marked-up copy indicating the amended paragraphs of the Specification is provided in an accompanying document.

On page 4, please delete the paragraph beginning on line 16, and substitute therefor:

12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000

Coal is often mined and used as a fuel within an electricity generating power plant. Most coal that is used as a fuel to generate electricity is mined. A significant number of coal formations are, however, not suitable for economical mining. For example, mining coal from steeply dipping coal seams, from relatively thin coal seams (e.g., less than about 1 meter thick), and/or from deep coal seams may not be economically feasible. Deep coal seams include coal seams that are at, or extend to, depths of greater than about 3000 feet (about 914 m) below surface level. The energy conversion efficiency of burning coal to generate electricity is relatively low, as compared to fuels such as natural gas. Also, burning coal to generate electricity often generates significant amounts of carbon dioxide, oxides of sulfur, and oxides of nitrogen that are released into the atmosphere.

On page 17, please delete the paragraph beginning on line 19, and substitute therefor:

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000

Controlling formation conditions to control the pressure of hydrogen in the produced fluid may result in improved qualities of the produced fluids. In some embodiments it may be desirable to control formation conditions so that the partial pressure of hydrogen in a produced fluid is greater than about 0.5 bars absolute, as measured at a production well.

On page 18, please delete the paragraph beginning on line 14, and substitute therefor:

A4  
In certain embodiments, a majority of the hydrocarbons in produced fluid may have a carbon number of less than approximately 25. Alternatively, less than about 15 weight % of the hydrocarbons in the fluid may have a carbon number greater than approximately 25. In other embodiments fluid produced may have a weight ratio of hydrocarbons having carbon numbers from 2 through 4, to methane, of greater than approximately 1 (e.g., for oil shale and heavy hydrocarbons) or greater than approximately 0.3 (e.g., for coal). The non-condensable hydrocarbons may include, but are not limited to, hydrocarbons having carbon numbers less than 5.

P5  
On page 29, please delete the paragraph beginning on line 31, and substitute therefor:

FIGS. 3a-3c depict embodiments of heater wells;

M4  
On page 30, please delete the six paragraphs beginning on line 12, and substitute therefor:

FIG. 11 depicts a portion of an overburden of a formation with a natural distributed combustor heat source;

FIG. 12 and FIG. 13 depict alternate embodiments of a natural distributed combustor heat source;

FIG. 14 and FIG. 15 depict embodiments of a natural distributed combustor system for heating a formation;

FIGS. 16-18 depict several embodiments of an insulated conductor heat source;

FIG. 19 depicts an embodiment of a conductor-in-conduit heat source in a formation;

FIG. 20 depicts an embodiment of a sliding connector;

FIG. 21 depicts an embodiment of a wellhead with a conductor-in-conduit heat source;

FIG. 22 and FIGS. 23a-23b depict several embodiments of a centralizer;

FIG. 24 depicts an alternate embodiment of a conductor-in-conduit heat source in a formation;

On page 32, please delete the paragraph beginning on line 10, and substitute therefor:

A7  
FIG. 81 depicts a comparison plot between the average pattern temperature and temperatures at various spots within triangular and hexagonal patterns of heat sources;

On page 32, please delete the twelve paragraphs beginning on line 22, and substitute therefor:

AB  
FIG. 90 depicts pressure versus temperature in an oil shale formation during pyrolysis;

FIG. 91 depicts quality of oil produced from an oil shale formation;

FIG. 92 depicts ethene to ethane ratio produced from an oil shale formation as a function of temperature and pressure;

FIG. 93 depicts yield of fluids produced from an oil shale formation as a function of temperature and pressure;

FIG. 94 depicts a plot of oil yield produced from treating an oil shale formation;

FIG. 95 depicts yield of oil produced from treating an oil shale formation;

FIG. 96 depicts hydrogen to carbon ratio of hydrocarbon condensate produced from an oil shale formation as a function of temperature and pressure;

FIG. 97 depicts olefin to paraffin ratio of hydrocarbon condensate produced from an oil shale formation as a function of pressure and temperature;

FIG. 98 depicts relationships between properties of a hydrocarbon fluid produced from an oil shale formation;

FIG. 99 depicts quantity of oil produced from an oil shale formation as a function of partial pressure of H<sub>2</sub>;

FIG. 100 depicts ethene to ethane ratios of fluid produced from an oil shale formation as a function of temperature and pressure;

88  
FIG. 101 depicts hydrogen to carbon atomic ratios of fluid produced from an oil shale formation as a function of temperature and pressure;

---

On page 33, please delete the paragraph beginning on line 15, and substitute therefor:

---

89  
FIG. 104 depicts a heat source and production well pattern for a field experiment in an oil shale formation;

---

On page 33, please delete the seven paragraphs beginning on line 18, and substitute therefor:

---

90  
FIG. 106 depicts a plot of temperature within the oil shale formation during the field experiment;

FIG. 107 depicts pressure within the oil shale formation during the field experiment;

FIG. 108 depicts a plot of API gravity of a fluid produced from the oil shale formation during the field experiment versus time;

FIG. 109 depicts average carbon numbers of fluid produced from the oil shale formation during the field experiment versus time;

FIG. 110 depicts density of fluid produced from the oil shale formation during the field experiment versus time;

FIG. 111 depicts a plot of weight percent of hydrocarbons within fluid produced from the oil shale formation during the field experiment;

FIG. 112 depicts a plot of an average yield of oil from the oil shale formation during the field experiment;

---

On page 34, please delete the paragraph beginning on line 2, and substitute therefor:

---

91  
FIG. 114 depicts total hydrocarbon production and liquid phase fraction versus time of a fluid produced from an oil shale formation;

---

On page 34, please delete the paragraph beginning on line 18, and substitute therefor:

FIG. 126 depicts yield of oil from a coal formation as a function of vitrinite reflectance;

On page 34, please delete the paragraph beginning on line 21, and substitute therefor:

FIG. 128 depicts CO<sub>2</sub> yield versus atomic O/C ratio for a coal formation;

On page 35, please delete the paragraph beginning on line 11, and substitute therefor:

FIG. 142 depicts weight percent of a hydrocarbon produced from two laboratory experiments on coal from the field test site versus carbon number distribution;

On page 35, please delete the three paragraphs beginning on line 15, and substitute therefor:

FIG. 144 depicts percentage ethene to ethane produced from a coal formation as a function of heating rate in an experimental field test;

FIG. 145 depicts product quality of fluids produced from a coal formation as a function of heating rate in an experimental field test;

FIG. 146 depicts weight percentages of various fluids produced from a coal formation for various heating rates in an experimental field test;

On page 35, please delete the five paragraphs beginning on line 23, and substitute therefor:

FIG. 148 depicts volatiles produced from a coal formation in an experimental field test versus cumulative energy content;

FIG. 149 depicts volume of gas produced from a coal formation in an experimental field test as a function of time;

AK4  
FIG. 150 depicts volume of oil produced from a coal formation in an experimental field test as a function of energy input;

FIG. 151 depicts synthesis gas production from the coal formation in an experimental field test versus the total water inflow;

FIG. 152 depicts additional synthesis gas production from the coal formation in an experimental field test due to injected steam;

On page 36, please delete the paragraph beginning on line 13, and substitute therefor:

A17  
FIG. 161 depicts an example of pyrolysis and synthesis gas production stages in a coal formation;

On page 36, please delete the paragraph beginning on line 19, and substitute therefor:

A18  
FIG. 165 depicts a plot of cumulative adsorbed methane and carbon dioxide versus pressure in a coal formation;

On page 46, please delete the two paragraphs beginning on line 18, and substitute therefor:

A19  
Formation fluids including pyrolyzation fluids may be produced from the formation. The pyrolyzation fluids may include, but are not limited to, hydrocarbons, hydrogen, carbon dioxide, carbon monoxide, hydrogen sulfide, ammonia, nitrogen, water and mixtures thereof. As the temperature of the formation increases, the amount of condensable hydrocarbons in the produced formation fluid tends to decrease, and the formation will in many instances tend to produce mostly methane and hydrogen. If a hydrocarbon containing formation is heated throughout an entire pyrolysis range, the formation may produce only small amounts of hydrogen towards an upper limit of the pyrolysis range. After all of the available hydrogen is depleted, a minimal amount of fluid production from the formation will typically occur.

119  
After pyrolysis of hydrocarbons, a large amount of carbon and some hydrogen may still be present in the formation. A significant portion of remaining carbon in the formation can be produced from the formation in the form of synthesis gas. Synthesis gas generation may take place during stage 3 heating as shown in FIG. 1. Stage 3 may include heating a hydrocarbon containing formation to a temperature sufficient to allow synthesis gas generation. For example, synthesis gas may be produced within a temperature range from about 400 °C to about 1200 °C. The temperature of the formation when the synthesis gas generating fluid is introduced to the formation will in many instances determine the composition of synthesis gas produced within the formation. If a synthesis gas generating fluid is introduced into a formation at a temperature sufficient to allow synthesis gas generation, then synthesis gas may be generated within the formation. The generated synthesis gas may be removed from the formation. A large volume of synthesis gas may be produced during generation of synthesis gas.

120  
On page 48, please delete the paragraph beginning on line 1, and substitute therefor:

121  
A van Krevelen diagram may be useful for selecting a resource for practicing various embodiments described herein (see discussion below). Treating a formation containing kerogen in region 5 will in many instances produce, e.g., carbon dioxide, non-condensable hydrocarbons, hydrogen, and water, along with a relatively small amount of condensable hydrocarbons. Treating a formation containing kerogen in region 7 will in many instances produce, e.g., carbon, condensable and non-condensable hydrocarbons, carbon dioxide, hydrogen, and water. Treating a formation containing kerogen in region 9 will in many instances produce, e.g., methane and hydrogen. A formation containing kerogen in region 7, for example, may in many instances be selected for treatment because doing so will tend to produce larger quantities of valuable hydrocarbons, and lower quantities of undesirable products such as carbon dioxide and water, since the region 7 kerogen has already undergone dehydration and/or decarboxylation over



A20  
geological time. In addition, region 7 kerogen can also be further treated to make other useful products (e.g., methane, hydrogen, and/or synthesis gas) as such kerogen transforms to region 9 kerogen.

On page 49, please delete the paragraph beginning on line 15, and substitute therefor:

A21  
Kerogen in region 9 may be treated to generate methane and hydrogen. For example, if such kerogen was previously treated (e.g., it was previously region 7 kerogen), then after pyrolysis, longer hydrocarbon chains of the hydrocarbons may have already cracked and been produced from the formation. Carbon and hydrogen, however, may still be present in the formation.

On page 50, please delete the paragraph beginning on line 5, and substitute therefor:

A22  
Kerogen is composed of organic matter that has been transformed due to a maturation process. Hydrocarbon containing formations that include kerogen may include, but are not limited to, coal formations and oil shale formations. Examples of hydrocarbon containing formations that may not include kerogen are formations containing heavy hydrocarbons (e.g., tar sands). The maturation process may include two stages: a biochemical stage and a geochemical stage. The biochemical stage typically involves degradation of organic material by both aerobic and anaerobic organisms. The geochemical stage typically involves conversion of organic matter due to temperature changes and significant pressures. During maturation, oil and gas may be produced as the organic matter of the kerogen is transformed.

On page 51, please delete the three paragraphs beginning on line 10, and substitute therefor:

A23  
The dashed lines in FIG. 2 correspond to vitrinite reflectance. The vitrinite reflectance is a measure of maturation. As kerogen undergoes maturation, the composition of the kerogen

P23

usually changes. For example, as kerogen undergoes maturation, volatile matter of kerogen tends to decrease. Rank classifications of kerogen indicate the level to which kerogen has matured. For example, as kerogen undergoes maturation, the rank of kerogen increases. Therefore, as rank increases, the volatile matter of kerogen tends to decrease. In addition, the moisture content of kerogen generally decreases as the rank increases. At higher ranks, however, the moisture content may become relatively constant. For example, higher rank kerogens that have undergone significant maturation, such as semi-anthracite or anthracite coal, tend to have a higher carbon content and a lower volatile matter content than lower rank kerogens such as lignite. For example, rank stages of coal formations include the following classifications, which are listed in order of increasing rank and maturity for type III kerogen: wood, peat, lignite, sub-bituminous coal, high volatile bituminous coal, medium volatile bituminous coal, low volatile bituminous coal, semi-anthracite, and anthracite. In addition, as rank increases, kerogen tends to exhibit an increase in aromatic nature.

Hydrocarbon containing formations may be selected for in situ treatment based on properties of at least a portion of the formation. For example, a formation may be selected based on richness, thickness, and depth (i.e., thickness of overburden) of the formation. In addition, a formation may be selected that will have relatively high quality fluids produced from the formation. In certain embodiments the quality of the fluids to be produced may be assessed in advance of treatment, thereby generating significant cost savings since only more optimal formations will be selected for treatment. Properties that may be used to assess hydrocarbons in a formation include, but are not limited to, an amount of hydrocarbon liquids that tend to be produced from the hydrocarbons, a likely API gravity of the produced hydrocarbon liquids, an amount of hydrocarbon gas that tends to be produced from the hydrocarbons, and/or an amount of carbon dioxide and water that tend to be produced from the hydrocarbons.

A23

Another property that may be used to assess the quality of fluids produced from certain kerogen containing formations is vitrinite reflectance. Such formations include, but are not limited to, coal formations and oil shale formations. Hydrocarbon containing formations that include kerogen can typically be assessed/selected for treatment based on a vitrinite reflectance of the kerogen. Vitrinite reflectance is often related to a hydrogen to carbon atomic ratio of a kerogen and an oxygen to carbon atomic ratio of the kerogen, as shown by the dashed lines in Fig. 2. For example, a van Krevelen diagram may be useful in selecting a resource for an in situ conversion process.

---

A24

On page 57, please delete the paragraph beginning on line 14, and substitute therefor:

---

Dewatering wells 110 may be placed in one or more rings surrounding selected portions of the formation. New dewatering wells may need to be installed as an area being treated by the in situ conversion process expands. An outermost row of dewatering wells may inhibit a significant amount of water from flowing into the portion of formation that is heated or to be heated. Water produced from the outermost row of dewatering wells should be substantially clean, and may require little or no treatment before being released. An innermost row of dewatering wells may inhibit water that bypasses the outermost row from flowing into the portion of formation that is heated or to be heated. The innermost row of dewatering wells may also inhibit outward migration of vapor from a heated portion of the formation into surrounding portions of the formation. Water produced by the innermost row of dewatering wells may include some hydrocarbons. The water may need to be treated before being released. Alternately, water with hydrocarbons may be stored and used to produce synthesis gas from a portion of the formation during a synthesis gas phase of the in situ conversion process. The dewatering wells may reduce heat loss to surrounding portions of the formation, may increase production of vapors from the heated portion, and may inhibit contamination of a water table proximate the heated portion of the formation.

---

On page 58, please delete the paragraph beginning on line 6, and substitute therefor:

125  
The hydrocarbons to be treated may be located under a large area. The in situ conversion system may be used to treat small portions of the formation, and other sections of the formation may be treated as time progresses. In an embodiment of a system for treating an oil shale formation, a field layout for 24 years of development may be divided into 24 individual plots that represent individual drilling years. Each plot may include 120 "tiles" (repeating matrix patterns) wherein each tile is made of 6 rows by 20 columns. Each tile may include 1 production well and 12 or 18 heater wells. The heater wells may be placed in an equilateral triangle pattern with, for example, a well spacing of about 12 m. Production wells may be located in centers of equilateral triangles of heater wells, or the production wells may be located approximately at a midpoint between two adjacent heater wells.

On page 59, please delete the paragraph beginning on line 15, and substitute therefor:

126  
In certain embodiments a first portion of a heater well may extend from a surface of the ground, through an overburden, and into a hydrocarbon containing formation. A second portion of the heater well may include one or more heater wells in the hydrocarbon containing formation. The one or more heater wells may be disposed within the hydrocarbon containing formation at various angles. In some embodiments, at least one of the heater wells may be disposed substantially parallel to a boundary of the hydrocarbon containing formation. In alternate embodiments, at least one of the heater wells may be substantially perpendicular to the hydrocarbon containing formation. In addition, one of the one or more heater wells may be positioned at an angle between perpendicular and parallel to a layer in the formation.

On page 63, please delete the two paragraphs beginning on line 8, and substitute therefor:

[illegible]

On page 64, please delete the paragraph beginning on line 24, and substitute therefor:

128

129

[illegible]

129

Triangular patterns tend to provide more uniform heating to a portion of the formation in comparison to other patterns such as squares and/or hexagons. Triangular patterns tend to provide faster heating to a predetermined temperature in comparison to other patterns such as squares and/or hexagons. Triangle patterns may also result in a small volume of the portion that is overheated. A plurality of units of heat sources such as triangular pattern 401 may be arranged substantially adjacent to each other to form a repetitive pattern of units over an area of the formation. For example, triangular patterns 401 may be arranged substantially adjacent to each other in a repetitive pattern of units by inverting an orientation of adjacent triangles 401. Other

patterns of heat sources 400 may also be arranged such that smaller patterns may be disposed adjacent to each other to form larger patterns.

On page 69, please delete the paragraph beginning on line 18, and substitute therefor:

A30  
For certain thinner formations, heating wells may be placed closer to an edge of the formation (e.g., in a staggered line instead of a line placed in the center of the layer) of the formation to increase the amount of hydrocarbons produced per unit of energy input. A portion of input heating energy may heat non-hydrocarbon containing formation, but the staggered pattern may allow superposition of heat to heat a majority of the hydrocarbon formation to pyrolysis temperatures. If the thin formation is heated by placing one or more heater wells in the formation along a center of the thickness, a significant portion of the hydrocarbon containing formation may not be heated to pyrolysis temperatures. In some embodiments, placing heater wells closer to an edge of the formation may increase the volume of formation undergoing pyrolysis per unit of energy input.

On page 78, please delete the paragraph beginning on line 17, and substitute therefor:

A31  
With time, reaction zone 524 may slowly extend radially to greater diameters from opening 514 as hydrocarbons are oxidized. Reaction zone 524 may, in many embodiments, maintain a relatively constant width. For example, reaction zone 524 may extend radially at a rate of less than about 0.91 m per year for a hydrocarbon containing formation. For example, for a coal formation, reaction zone 524 may extend radially at a rate between about 0.5 m per year to about 1 m per year. For an oil shale formation, reaction zone 524 may extend radially about 2 m in the first year and at a lower rate in subsequent years due to an increase in volume of reaction zone 524 as reaction zone 524 extends radially. Such a lower rate may be about 1 m per year to about 1.5 m per year. Reaction zone 524 may extend at slower rates for hydrocarbon rich formations (e.g., coal) and at faster rates for formations with more inorganic material in it (e.g.,

oil shale) since more hydrocarbons per volume are available for combustion in the hydrocarbon rich formations.

On page 81, please delete the paragraph beginning on line 8, and substitute therefor:

A32  
In certain embodiments one or more natural distributed combustors may be placed along strike and/or horizontally. Doing so tends to reduce pressure differentials along the heated length of the well. The absence of pressure differentials may make controlling the temperature generated along a length of the heater more uniform and easier to control.

A33  
On page 87, please delete the paragraph beginning on line 16, and substitute therefor:

In certain embodiments, insulated conductor heaters may be placed in wellbores without support members and/or centralizers. This can be accomplished for heaters if the insulated conductor has a suitable combination of temperature and corrosion resistance, creep strength, length, thickness (diameter) and metallurgy that will inhibit failure of the insulated conductor during use. In an embodiment, insulated conductors that are heated to a working temperature of about 700 °C are less than about 150 meters in length, are made of 310 stainless steel, and may be used without support members.

A34  
On page 100, please delete the paragraph beginning on line 18, and substitute therefor:

In an embodiment, a control system may be configured to control electrical power supplied to an insulated conductor heater. Power supplied to the insulated conductor heater may be controlled with any appropriate type of controller. For alternating current, the controller may, for example, be a tapped transformer. Alternatively, the controller may be a zero crossover electrical heater firing SCR (silicon controlled rectifier) controller. Zero crossover electrical heater firing control may be achieved by allowing full supply voltage to the insulated conductor heater to pass through the insulated conductor heater for a specific number of cycles, starting at



A34

the "crossover," where an instantaneous voltage may be zero, continuing for a specific number of complete cycles, and discontinuing when the instantaneous voltage again may cross zero. A specific number of cycles may be blocked, allowing control of the heat output by the insulated conductor heater. For example, the control system may be arranged to block fifteen and/or twenty cycles out of each sixty cycles that may be supplied by a standard 60 Hz alternating current power supply. Zero crossover firing control may be advantageously used with materials having low temperature coefficient materials. Zero crossover firing control may substantially inhibit current spikes from occurring in an insulated conductor heater.

A35

On page 101, please delete the paragraph beginning on line 23, and substitute therefor:

Conductor 580 may be centered in conduit 582 through centralizer 581. Centralizer 581 may electrically isolate conductor 580 from conduit 582. In addition, centralizer 581 may be configured to locate conductor 580 within conduit 582. Centralizer 581 may be made of a ceramic material or a combination of ceramic and metallic materials. More than one centralizer 581 may be configured to substantially inhibit deformation of conductor 580 in conduit 582 during use. More than one centralizer 581 may be spaced at intervals between approximately 0.5 m and approximately 3 m along conductor 580. Centralizer 581 may be made of ceramic, 304 stainless steel, 310 stainless steel, or other types of metal. Centralizer 581 may be configured as shown in FIG. 22 and/or FIGS. 23a and 23b.

A36

On page 102, please delete the paragraph beginning on line 2, and substitute therefor:

As depicted in FIG. 20, sliding connector 583 may couple an end of conductor 580 disposed proximate a lowermost surface of conduit 582. Sliding connector 583 allows for differential thermal expansion between conductor 580 and conduit 582. Sliding connector 583 is attached to a conductor 580 located at the bottom of the well at a low resistance section 584 which may have a greater cross-sectional area. The lower resistance of section 584 allows the

134  
sliding connector to operate at temperatures no greater than about 90 °C. In this manner, corrosion of the sliding connector components is minimized and therefore contact resistance between sliding connector 583 and conduit 582 is also minimized. Sliding connector 583 may be configured as shown in FIG. 20 and as described in any of the embodiments herein. The substantially low resistance section 584 of the conductor 580 may couple conductor 580 to wellhead 690 as depicted in FIG. 19. Wellhead 690 may be configured as shown in FIG. 21 and as described in any of the embodiments herein. As depicted in FIG. 19, electrical current may be applied to conductor 580 from power cable 585 through a low resistance section 584 of the conductor 580. Electrical current may pass from conductor 580 through sliding connector 583 to conduit 582. Conduit 582 may be electrically insulated from overburden casing 541 and from wellhead 690 to return electrical current to power cable 585. Heat may be generated in conductor 580 and conduit 582. The generated heat may radiate within conduit 582 and opening 514 to heat at least a portion of formation 516. As an example, a voltage of about 330 volts and a current of about 795 amps may be supplied to conductor 580 and conduit 582 in a 229 m (750 ft) heated section to generate about 1150 watts/meter of conductor 580 and conduit 582.

135  
On page 111, please delete the paragraph beginning on line 24, and substitute therefor:

137  
An elongated member may have a length of about 650 meters. Longer lengths may be achieved using sections of high strength alloys, but such elongated members may be expensive. In some embodiments, an elongated member may be supported by a plate in a wellhead. The elongated member may include sections of different conductive materials that are welded together end-to-end. A large amount of electrically conductive weld material may be used to couple the separate sections together to increase strength of the resulting member and to provide a path for electricity to flow that will not result in arcing and/or corrosion at the welded connections. The different conductive materials may include alloys with a high creep resistance. The sections of different conductive materials may have varying diameters to ensure uniform

AB1  
deletion  
heating along the elongated member. A first metal that has a higher creep resistance than a second metal typically has a higher resistivity than the second metal. The difference in resistivities may allow a section of larger cross sectional area, more creep resistant, first metal to dissipate the same amount of heat as a section of smaller cross sectional area, second metal. The cross sectional areas of the two different metals may be tailored to result in substantially the same amount of heat dissipation in two welded together sections of the metals. The conductive materials may include, but are not limited to, 617 Inconel, HR-120, 316 stainless steel, and 304 stainless steel. For example, an elongated member may have a 60 meter section of 617 Inconel, 60 meter section of HR-120, and 150 meter section of 304 stainless steel. In addition, the elongated member may have a low resistance section that may run from the wellhead through the overburden. This low resistance section may decrease the heating within the formation from the wellhead through the overburden. The low resistance section may be the result of, for example, choosing a substantially electrically conductive material and/or increasing the cross-sectional area available for electrical conduction.

AB2  
deletion  
On page 118, please delete the paragraph beginning on line 4, and substitute therefor:

Inner conduit 612 may be configured to provide oxidation products 613 into outer conduit 615 proximate a bottom of opening 614. Inner conduit 612 may have insulation 612a. FIG. 27 illustrates an embodiment of inner conduit 612 with insulation 612a and ceramic insulator 612b disposed on an inner surface of inner conduit 612. Insulation 612a may be configured to substantially inhibit heat transfer between fluids in inner conduit 612 and fluids in outer conduit 615. A thickness of insulation 612a may be varied along a length of inner conduit 612 such that heat transfer to formation 516 may vary along the length of inner conduit 612. For example, a thickness of insulation 612a may be tapered from a larger thickness to a lesser thickness from a top portion to a bottom portion, respectively, of inner conduit 612 in opening 614. Such a tapered thickness may provide substantially more uniform heating of formation 516.

A38  
along the length of inner conduit 612 in opening 614. Insulation 612a may include ceramic and metal materials. Oxidation products 613 may return to surface 550 through outer conduit 615. Outer conduit may have insulation 615a as depicted in FIG. 26. Insulation 615a may be configured to substantially inhibit heat transfer from outer conduit 615 to overburden 540.

On page 124, please delete the paragraph beginning on line 13, and substitute therefor:

A39  
It is to be understood that the above equations can be used to assess or estimate temperatures, average temperatures (e.g., over selected sections of the formation), heat input, etc. Such equations do not take into account other factors (such as heat losses), which would also have some effect on heating and temperatures assessments. However such factors can ordinarily be addressed with correction factors, as is commonly done in the art.

On pages 134 to 135, please delete Tables 1a and 1b, and substitute therefor:

TABLE 1a

A40

PROPERTY	$a_1$	$a_2$	$a_3$	$a_4$
API Gravity	-0.738549	-8.893902	4752.182	-145484.6
Ethene/Ethane Ratio	-15543409	3261335	-303588.8	-2767.469
Weight Percent of Hydrocarbons Having a Carbon Number Greater Than 25	0.1621956	-8.85952	547.9571	-24684.9
Atomic H/C Ratio	2950062	-16982456	32584767	-20846821
Liquid Production (gal/ton)	119.2978	-5972.91	96989	-524689
Equivalent Liquid Production (gal/ton)	-6.24976	212.9383	-777.217	-39353.47
% Fischer Assay	0.5026013	-126.592	9813.139	-252736

TABLE 1b

PROPERTY	$b_1$	$b_2$	$b_3$	$b_4$
API Gravity	0.003843	-0.279424	3.391071	96.67251
Ethene/Ethane Ratio	-8974.317	2593.058	-40.78874	23.31395
Weight Percent of Hydrocarbons Having a Carbon Number Greater Than 25	-0.0005022	0.026258	-1.12695	44.49521
Atomic H/C Ratio	790.0532	-4199.454	7328.572	-4156.599
Liquid Production (gal/ton)	-0.17808	8.914098	-144.999	793.2477
Equivalent Liquid Production (gal/ton)	-0.03387	2.778804	-72.6457	650.7211
% Fischer Assay	-0.0007901	0.196296	-15.1369	395.3574

On page 141, please delete the paragraph beginning on line 16, and substitute therefor:

In some embodiments, the non-condensable hydrocarbons may include, but are not limited to, hydrocarbons having less than about 5 carbon atoms, H<sub>2</sub>, CO<sub>2</sub>, ammonia, H<sub>2</sub>S, N<sub>2</sub> and/or CO. In certain embodiments, non-condensable hydrocarbons of a fluid produced from a portion of a hydrocarbon containing formation may have a weight ratio of hydrocarbons having carbon numbers from 2 through 4 ("C<sub>2-4</sub>" hydrocarbons) to methane of greater than about 0.3, greater than about 0.75, or greater than about 1 in some circumstances. For example, non-condensable hydrocarbons of a fluid produced from a portion of an oil shale or heavy hydrocarbon containing formation may have a weight ratio of hydrocarbons having carbon numbers from 2 through 4, to methane, of greater than approximately 1. In addition, non-condensable hydrocarbons of a fluid produced from a portion of a coal formation may have a

weight ratio of hydrocarbons having carbon numbers from 2 through 4, to methane, of greater than approximately 0.3.

On page 142, please delete the paragraph beginning on line 23, and substitute therefor:

The non-condensable hydrocarbons of fluid produced from a hydrocarbon containing formation may have a H<sub>2</sub> content of greater than about 5 % by weight, greater than about 10 % by weight, or even greater than about 15 % by weight. The H<sub>2</sub> may be used, for example, as a fuel for a fuel cell, to hydrogenate hydrocarbon fluids in situ, and/or to hydrogenate hydrocarbon fluids ex situ. In addition, presence of H<sub>2</sub> within a formation fluid in a heated section of a hydrocarbon containing formation is believed to increase the quality of produced fluids. In certain embodiments, the hydrogen to carbon atomic ratio of a produced fluid may be at least approximately 1.7 or above. For example, the hydrogen to carbon atomic ratio of a produced fluid may be approximately 1.8, approximately 1.9, or greater.

On page 144, please delete the paragraph beginning on line 4, and substitute therefor:

In certain embodiments, a fluid produced from a formation (e.g., a coal formation) may include oxygenated hydrocarbons. For example, condensable hydrocarbons of the produced fluid may include an amount of oxygenated hydrocarbons greater than about 5 % by weight of the condensable hydrocarbons. Alternatively, the condensable hydrocarbons may include an amount of oxygenated hydrocarbons greater than about 1.0 % by weight of the condensable hydrocarbons. Furthermore, the condensable hydrocarbons may include an amount of oxygenated hydrocarbons greater than about 1.5 % by weight of the condensable hydrocarbons or greater than about 2.0 % by weight of the condensable hydrocarbons. In an embodiment, the oxygenated hydrocarbons may include, but are not limited to, phenol and/or substituted phenols. In some embodiments, phenol and substituted phenols may have more economic value than other products produced from an in situ conversion process. Therefore, an in situ conversion

On page 146, please delete the paragraph beginning on line 15, and substitute therefor:

In certain embodiments, the condensable hydrocarbons of a fluid produced from a formation may include compounds containing oxygen. For example, in certain embodiments (e.g., for oil shale and heavy hydrocarbons) less than about 1 % by weight (when calculated on an elemental basis) of the condensable hydrocarbons may be oxygen containing compounds (e.g., typically the oxygen may be in oxygen containing compounds such as phenol, substituted phenols, ketones, etc.). In certain other embodiments, (e.g., for coal formations) between about 5 % by weight and about 30 % by weight of the condensable hydrocarbons may typically include oxygen containing compounds such as phenols, substituted phenols, ketones, etc. In some instances, certain compounds containing oxygen (e.g., phenols) may be valuable and, as such, may be economically separated from the produced fluid.

On page 149, please delete the paragraph beginning on line 30, and substitute therefor:

Thermal diffusivity within a hydrocarbon containing formation may vary depending on, for example, a density of the hydrocarbon containing formation, a heat capacity of the formation, and a thermal conductivity of the formation. As pyrolysis occurs within a selected section, the hydrocarbon containing mass may be removed from the selected section. The removal of mass may include, but is not limited to, removal of water and a transformation of hydrocarbons to formation fluids. For example, a lower thermal conductivity may be expected as water is removed from a coal formation. This effect may vary significantly at different depths. At greater depths a lithostatic pressure may be higher, and may close certain openings (e.g., cleats and/or fractures) in the coal. The closure of the coal openings may increase a thermal

conductivity of the coal. In some embodiments, a higher thermal conductivity may be observed due to a higher lithostatic pressure.

On page 152, please delete the paragraph beginning on line 15, and substitute therefor:

Substantially uniform heating of the hydrocarbon containing formation may result in a substantially uniform increase in permeability. For example, uniformly heating may generate a series of substantially uniform fractures within the heated portion due to thermal stresses generated in the formation. Heating substantially uniformly may generate pyrolysis fluids from the portion in a substantially homogeneous manner. Water removed due to vaporization and production may result in increased permeability of the heated portion. In addition to creating fractures due to thermal stresses, fractures may also be generated due to fluid pressure increase. As fluids are generated within the heated portion, a fluid pressure within the heated portion may also increase. As the fluid pressure approaches a lithostatic pressure of the heated portion, fractures may be generated. Substantially uniform heating and homogeneous generation of fluids may generate substantially uniform fractures within the heated portion. In some embodiments, a permeability of a heated section of a hydrocarbon containing formation may not vary by more than a factor of about 10.

On page 156, please delete the paragraph beginning on line 24, and substitute therefor:

Synthesis gas may be produced from a dipping formation from wells used during pyrolysis of the formation. As shown in FIG. 4, synthesis gas production wells 206 may be located above and down dip from an injection well 202. Hot synthesis gas producing fluid may be introduced into injection well 202. Hot synthesis gas fluid that moves down dip may generate synthesis gas that is produced through synthesis gas production wells 206. Synthesis gas generating fluid that moves up dip may generate synthesis gas in a portion of the formation that is at synthesis gas generating temperatures. A portion of the synthesis gas generating fluid and



247  
generated synthesis gas that moves up dip above the portion of the formation at synthesis gas generating temperatures may heat adjacent portions of the formation. The synthesis gas generating fluid that moves up dip may condense, heat adjacent portions of formation, and flow downwards towards or into a portion of the formation at synthesis gas generating temperature. The synthesis gas generating fluid may then generate additional synthesis gas.

---

On page 163, please delete the paragraph beginning on line 26, and substitute therefor:

---

248  
The first temperature may be substantially different than the second temperature. Alternatively, the first and second temperatures may be approximately the same temperature. For example, a temperature sufficient to allow generation of synthesis gas having different compositions may vary depending on compositions of the first and second portions and/or prior pyrolysis of hydrocarbons within the first and second portions. The first synthesis gas generating fluid may have substantially the same composition as the second synthesis gas generating fluid. Alternatively, the first synthesis gas generating fluid may have a different composition than the second synthesis gas generating fluid. Appropriate first and second synthesis gas generating fluids may vary depending upon, for example, temperatures of the first and second portions, compositions of the first and second portions, and prior pyrolysis of hydrocarbons within the first and second portions.

---

On page 166, please delete the paragraph beginning on line 2, and substitute therefor:

---

249  
FIG. 33 illustrates a reduced emission energy process. Carbon dioxide 928 produced by energy generation unit 902 may be separated from fluids exiting the energy generation unit. Carbon dioxide may be separated from H<sub>2</sub> at high temperatures by using a hot palladium film supported on porous stainless steel or a ceramic substrate, or high temperature pressure swing adsorption. The carbon dioxide may be sequestered in spent hydrocarbon containing formation 922, injected into oil producing fields 924 for enhanced oil recovery by improving mobility and

449  
production of oil in such fields, sequestered into a deep hydrocarbon containing formation 926 containing methane by adsorption and subsequent desorption of methane, or re-injected 928 into a section of the formation through a synthesis gas production well to produce carbon monoxide. Carbon dioxide leaving the energy generation unit may be sequestered in a dewatered coal bed methane reservoir. The water for synthesis gas generation may come from dewatering a coal bed methane reservoir. Additional methane can also be produced by alternating carbon dioxide and nitrogen. An example of a method for sequestering carbon dioxide is illustrated in U.S. Pat. No. 5,566,756 to Chaback et al., which is incorporated by reference as if fully set forth herein. Additional energy may be utilized by removing heat from the carbon dioxide stream leaving the energy generation unit.

---

105007-1211500  
On page 166, please delete the paragraph beginning on line 27, and substitute therefor:

---

450  
In one embodiment, a spent hydrocarbon containing formation may be mined. The mined material may in some embodiments be used for metallurgical purposes such as a fuel for generating high temperatures during production of steel. Pyrolysis of a coal formation may substantially increase a rank of the coal. After pyrolysis, the coal may be substantially transformed to a coal having characteristics of anthracite. A spent hydrocarbon containing formation may have a thickness of 30 m or more. Anthracite coal seams, which are typically mined for metallurgical uses, may be only about one meter in thickness.

---

451  
On page 178, please delete the paragraph beginning on line 4, and substitute therefor:

---

Ammonia and urea may be produced using a carbon containing formation, and using an O<sub>2</sub> rich stream and a N<sub>2</sub> rich stream. The O<sub>2</sub> rich stream and synthesis gas generating fluid may be provided to a formation. The formation may be heated, or partially heated, by oxidation of carbon in the formation with the O<sub>2</sub> rich stream. H<sub>2</sub> in the synthesis gas, and N<sub>2</sub> from the N<sub>2</sub> rich stream, may be provided to an ammonia synthesis process to generate ammonia.

---

On page 179, please delete the paragraph beginning on line 22, and substitute therefor:

AS2

FIG. 43 illustrates an embodiment of a method for preparing a nitrogen stream for an ammonia and urea process. Air 2060 may be injected into hot carbon containing formation 2062 to produce carbon dioxide by oxidation of carbon in the formation. In an embodiment, a heater may be configured to heat at least a portion of the carbon containing formation to a temperature sufficient to support oxidation of the carbon. The temperature sufficient to support oxidation may be, for example, about 260 °C for coal. Stream 2064 exiting the hot formation may be composed substantially of carbon dioxide and nitrogen. Nitrogen may be separated from carbon dioxide by passing the stream through cold spent carbon containing formation 2066. Carbon dioxide may be preferentially adsorbed versus nitrogen in the cold spent formation 2066. For example, at 50 °C and 0.35 bars, the adsorption of carbon dioxide on a spent portion of coal may be about 72 m<sup>3</sup>/metric ton compared to about 15.4 m<sup>3</sup>/metric ton for nitrogen. Nitrogen 2068 exiting the cold spent portion 2066 may be supplied to ammonia production facility 2070 with H<sub>2</sub> stream 2072 to produce ammonia 2074. The H<sub>2</sub> stream may be obtained by methods disclosed herein, for example, the methods described in FIGS. 41 and 42.

On page 188, please delete the paragraph beginning on line 25, and substitute therefor:

AS3

FIG. 50 illustrates an alternate embodiment of pattern 2406 of heat sources 2400 that may be arranged in a "7 spot" pattern with production well 2402. In the "7 spot" pattern, six heat sources 2400 may be arranged substantially equidistant from production well 2402 and substantially equidistant from each other as depicted in FIG. 50. Heat sources 2400 may also be configured as a production well. Also, production well 2402 may be configured as a heat source. A spacing between heat sources 2400 and production well 2402 may be determined as described in any of the above embodiments.

On page 191, please delete the paragraph beginning on line 8, and substitute therefor:

PS4  
In an embodiment, condensable hydrocarbons of a fluid produced from a relatively permeable formation may include aromatic compounds. For example, greater than about 20 % by weight of the condensable hydrocarbons may include aromatic compounds. In another embodiment, an aromatic compound weight percent may include greater than about 30 % of the condensable hydrocarbons. The condensable hydrocarbons may also include di-aromatic compounds. For example, less than about 20 % by weight of the condensable hydrocarbons may include di-aromatic compounds. In another embodiment, di-aromatic compounds may include less than about 15 % by weight of the condensable hydrocarbons. The condensable hydrocarbons may also include tri-aromatic compounds. For example, less than about 4 % by weight of the condensable hydrocarbons may include tri-aromatic compounds. In another embodiment, less than about 1 % by weight of the condensable hydrocarbons may include tri-aromatic compounds.

On page 196, please delete the paragraph beginning on line 29, and substitute therefor:

PS5  
FIG. 53 is a view of an embodiment of a heat source and production well pattern illustrating a pyrolysis zone and a low viscosity zone. Heat sources 2512 along plane 2504 and plane 2506 may heat planar region 2508 to create a pyrolysis zone. Heating may create thermal fractures 2510 in the pyrolysis zone. Heating with heat sources 2514 in planes 2516, 2518, 2520, and 2522 may create a low viscosity zone with an increased permeability due to thermal fractures. Pressure differential between the low viscosity zone and the pyrolysis zone may force mobilized fluid from the low viscosity zone into the pyrolysis zone. The permeability created by thermal fractures 2510 may be sufficiently high to create a substantially uniform pyrolysis zone. Pyrolyzation fluids may be produced through production well 2500.

On page 202, please delete the paragraph beginning on line 9, and substitute therefor:

AS6  
FIGS. 62, 63, 64, and 65 illustrate alternate embodiments in which both production wells and heat sources may be located at the apices of a triangular grid. In FIG. 62, a triangular grid, with a spacing of  $s$ , may have production wells 2701 spaced at a distance of  $2s$ . A hexagonal pattern may include one ring 2730 of six heat sources 2732. Each heat source 2732 may provide substantially equal amounts of heat to two production wells 2701. Therefore, each ring 2730 of six heat sources 2732 contributes approximately three equivalent heat sources per production well 2701.

On page 211, please delete the paragraph beginning on line 2, and substitute therefor:

AS7  
FIG. 73 illustrates an embodiment of an additional processing unit that may be included in surface facilities 2800 such as the facilities depicted in FIG. 71. Air 2903 may be fed to air separation unit 2900. Air separation unit 2900 may be configured to generate nitrogen stream 2902 and oxygen stream 2905. Oxygen stream 2905 and steam 2904 may be injected into exhausted coal resource 2906 to generate synthesis gas 2907. Produced synthesis gas 2907 may be provided to Shell Middle Distillates process unit 2910 that may be configured to produce middle distillates 2912. In addition, produced synthesis gas 2907 may be provided to catalytic methanation process unit 2914 that may be configured to produce natural gas 2916. Produced synthesis gas 2907 may also be provided to methanol production unit 2918 to produce methanol 2920. Furthermore, produced synthesis gas 2907 may be provided to process unit 2922 for production of ammonia and/or urea 2924, and fuel cell 2926 that may be configured to produce electricity 2928. Synthesis gas 2907 may also be routed to power generation unit 2930, such as a turbine or combustor, to produce electricity 2932.

On page 213, please delete the paragraph beginning on line 16, and substitute therefor:

AS8  
FIG. 78 illustrates temperature profile 3110 after three years of heating for a triangular pattern with a 12.2 m spacing in a typical Green River oil shale. The triangular pattern may be

1758  
configured as shown in FIG. 76. Temperature profile 3110 is a three-dimensional plot of temperature versus a location within a triangular pattern. FIG. 79 illustrates temperature profile 3108 after three years of heating for a square pattern with 11.3 m spacing in a typical Green River oil shale. Temperature profile 3108 is a three-dimensional plot of temperature versus a location within a square pattern. The square pattern may be configured as shown in FIG. 76a. FIG. 79a illustrates temperature profile 3109 after three years of heating for a hexagonal pattern with 10.0 m spacing in a typical Green River oil shale. Temperature profile 3109 is a three-dimensional plot of temperature versus a location within a hexagonal pattern. The hexagonal pattern may be configured as shown in FIG. 77.

On page 215, please delete the paragraph beginning on line 2, and substitute therefor:

1759  
FIG. 81 illustrates a comparison plot between the average pattern temperature 3120 (in degrees Celsius), temperatures at coldest spot 3118 for triangular patterns, coldest spot 3114 for hexagonal patterns, point 3116 located at the center of a side of triangular pattern midway between heaters, and point 3112 located at the center of a side of hexagonal pattern midway between heaters, as a function of time (in years). FIG. 81a illustrates a comparison plot between the average pattern temperature 3120 (in degrees Celsius), temperatures at coldest spot 3117 and point 3119 located at the center of a side of a pattern midway between heaters, as a function of time (in years), for a square pattern.

On page 216, please delete the paragraph beginning on line 29, and substitute therefor:

1760  
A spacing of heat sources in a triangular pattern, which may yield the same process time as a hexagonal pattern having about a 10.0 m space between heat sources, may be equal to approximately 14.3 m. In this manner, the total process time of a triangular pattern may be achieved by using about 26 % less heat sources than may be included in a hexagonal pattern. In

160  
this manner, such a triangular pattern may have substantially lower capital and operating costs.  
As such, this triangular pattern may also be more economical than a hexagonal pattern.

On page 225, please delete the four paragraphs beginning on line 24, and substitute therefor:

1315  
FIG. 91 illustrates oil quality produced from an oil shale formation as a function of pressure and temperature. Lines indicating different oil qualities, as defined by API gravity, are plotted. For example, the quality of the produced oil was 45° API when pressure was maintained at about 6 bars absolute and a temperature was about 375 °C. As described in above embodiments, low pyrolysis temperatures and relatively high pressures may produce a high API gravity oil.

1320  
1325  
1330  
1335  
1340  
1345  
1350  
1355  
1360  
1365  
1370  
1375  
1380  
1385  
1390  
1395  
1400  
1405  
1410  
1415  
1420  
1425  
1430  
1435  
1440  
1445  
1450  
1455  
1460  
1465  
1470  
1475  
1480  
1485  
1490  
1495  
1500  
1505  
1510  
1515  
1520  
1525  
1530  
1535  
1540  
1545  
1550  
1555  
1560  
1565  
1570  
1575  
1580  
1585  
1590  
1595  
1600  
1605  
1610  
1615  
1620  
1625  
1630  
1635  
1640  
1645  
1650  
1655  
1660  
1665  
1670  
1675  
1680  
1685  
1690  
1695  
1700  
1705  
1710  
1715  
1720  
1725  
1730  
1735  
1740  
1745  
1750  
1755  
1760  
1765  
1770  
1775  
1780  
1785  
1790  
1795  
1800  
1805  
1810  
1815  
1820  
1825  
1830  
1835  
1840  
1845  
1850  
1855  
1860  
1865  
1870  
1875  
1880  
1885  
1890  
1895  
1900  
1905  
1910  
1915  
1920  
1925  
1930  
1935  
1940  
1945  
1950  
1955  
1960  
1965  
1970  
1975  
1980  
1985  
1990  
1995  
2000  
2005  
2010  
2015  
2020  
2025  
2030  
2035  
2040  
2045  
2050  
2055  
2060  
2065  
2070  
2075  
2080  
2085  
2090  
2095  
2100  
2105  
2110  
2115  
2120  
2125  
2130  
2135  
2140  
2145  
2150  
2155  
2160  
2165  
2170  
2175  
2180  
2185  
2190  
2195  
2200  
2205  
2210  
2215  
2220  
2225  
2230  
2235  
2240  
2245  
2250  
2255  
2260  
2265  
2270  
2275  
2280  
2285  
2290  
2295  
2300  
2305  
2310  
2315  
2320  
2325  
2330  
2335  
2340  
2345  
2350  
2355  
2360  
2365  
2370  
2375  
2380  
2385  
2390  
2395  
2400  
2405  
2410  
2415  
2420  
2425  
2430  
2435  
2440  
2445  
2450  
2455  
2460  
2465  
2470  
2475  
2480  
2485  
2490  
2495  
2500  
2505  
2510  
2515  
2520  
2525  
2530  
2535  
2540  
2545  
2550  
2555  
2560  
2565  
2570  
2575  
2580  
2585  
2590  
2595  
2600  
2605  
2610  
2615  
2620  
2625  
2630  
2635  
2640  
2645  
2650  
2655  
2660  
2665  
2670  
2675  
2680  
2685  
2690  
2695  
2700  
2705  
2710  
2715  
2720  
2725  
2730  
2735  
2740  
2745  
2750  
2755  
2760  
2765  
2770  
2775  
2780  
2785  
2790  
2795  
2800  
2805  
2810  
2815  
2820  
2825  
2830  
2835  
2840  
2845  
2850  
2855  
2860  
2865  
2870  
2875  
2880  
2885  
2890  
2895  
2900  
2905  
2910  
2915  
2920  
2925  
2930  
2935  
2940  
2945  
2950  
2955  
2960  
2965  
2970  
2975  
2980  
2985  
2990  
2995  
3000  
3005  
3010  
3015  
3020  
3025  
3030  
3035  
3040  
3045  
3050  
3055  
3060  
3065  
3070  
3075  
3080  
3085  
3090  
3095  
3100  
3105  
3110  
3115  
3120  
3125  
3130  
3135  
3140  
3145  
3150  
3155  
3160  
3165  
3170  
3175  
3180  
3185  
3190  
3195  
3200  
3205  
3210  
3215  
3220  
3225  
3230  
3235  
3240  
3245  
3250  
3255  
3260  
3265  
3270  
3275  
3280  
3285  
3290  
3295  
3300  
3305  
3310  
3315  
3320  
3325  
3330  
3335  
3340  
3345  
3350  
3355  
3360  
3365  
3370  
3375  
3380  
3385  
3390  
3395  
3400  
3405  
3410  
3415  
3420  
3425  
3430  
3435  
3440  
3445  
3450  
3455  
3460  
3465  
3470  
3475  
3480  
3485  
3490  
3495  
3500  
3505  
3510  
3515  
3520  
3525  
3530  
3535  
3540  
3545  
3550  
3555  
3560  
3565  
3570  
3575  
3580  
3585  
3590  
3595  
3600  
3605  
3610  
3615  
3620  
3625  
3630  
3635  
3640  
3645  
3650  
3655  
3660  
3665  
3670  
3675  
3680  
3685  
3690  
3695  
3700  
3705  
3710  
3715  
3720  
3725  
3730  
3735  
3740  
3745  
3750  
3755  
3760  
3765  
3770  
3775  
3780  
3785  
3790  
3795  
3800  
3805  
3810  
3815  
3820  
3825  
3830  
3835  
3840  
3845  
3850  
3855  
3860  
3865  
3870  
3875  
3880  
3885  
3890  
3895  
3900  
3905  
3910  
3915  
3920  
3925  
3930  
3935  
3940  
3945  
3950  
3955  
3960  
3965  
3970  
3975  
3980  
3985  
3990  
3995  
4000  
4005  
4010  
4015  
4020  
4025  
4030  
4035  
4040  
4045  
4050  
4055  
4060  
4065  
4070  
4075  
4080  
4085  
4090  
4095  
4100  
4105  
4110  
4115  
4120  
4125  
4130  
4135  
4140  
4145  
4150  
4155  
4160  
4165  
4170  
4175  
4180  
4185  
4190  
4195  
4200  
4205  
4210  
4215  
4220  
4225  
4230  
4235  
4240  
4245  
4250  
4255  
4260  
4265  
4270  
4275  
4280  
4285  
4290  
4295  
4300  
4305  
4310  
4315  
4320  
4325  
4330  
4335  
4340  
4345  
4350  
4355  
4360  
4365  
4370  
4375  
4380  
4385  
4390  
4395  
4400  
4405  
4410  
4415  
4420  
4425  
4430  
4435  
4440  
4445  
4450  
4455  
4460  
4465  
4470  
4475  
4480  
4485  
4490  
4495  
4500  
4505  
4510  
4515  
4520  
4525  
4530  
4535  
4540  
4545  
4550  
4555  
4560  
4565  
4570  
4575  
4580  
4585  
4590  
4595  
4600  
4605  
4610  
4615  
4620  
4625  
4630  
4635  
4640  
4645  
4650  
4655  
4660  
4665  
4670  
4675  
4680  
4685  
4690  
4695  
4700  
4705  
4710  
4715  
4720  
4725  
4730  
4735  
4740  
4745  
4750  
4755  
4760  
4765  
4770  
4775  
4780  
4785  
4790  
4795  
4800  
4805  
4810  
4815  
4820  
4825  
4830  
4835  
4840  
4845  
4850  
4855  
4860  
4865  
4870  
4875  
4880  
4885  
4890  
4895  
4900  
4905  
4910  
4915  
4920  
4925  
4930  
4935  
4940  
4945  
4950  
4955  
4960  
4965  
4970  
4975  
4980  
4985  
4990  
4995  
5000  
5005  
5010  
5015  
5020  
5025  
5030  
5035  
5040  
5045  
5050  
5055  
5060  
5065  
5070  
5075  
5080  
5085  
5090  
5095  
5100  
5105  
5110  
5115  
5120  
5125  
5130  
5135  
5140  
5145  
5150  
5155  
5160  
5165  
5170  
5175  
5180  
5185  
5190  
5195  
5200  
5205  
5210  
5215  
5220  
5225  
5230  
5235  
5240  
5245  
5250  
5255  
5260  
5265  
5270  
5275  
5280  
5285  
5290  
5295  
5300  
5305  
5310  
5315  
5320  
5325  
5330  
5335  
5340  
5345  
5350  
5355  
5360  
5365  
5370  
5375  
5380  
5385  
5390  
5395  
5400  
5405  
5410  
5415  
5420  
5425  
5430  
5435  
5440  
5445  
5450  
5455  
5460  
5465  
5470  
5475  
5480  
5485  
5490  
5495  
5500  
5505  
5510  
5515  
5520  
5525  
5530  
5535  
5540  
5545  
5550  
5555  
5560  
5565  
5570  
5575  
5580  
5585  
5590  
5595  
5600  
5605  
5610  
5615  
5620  
5625  
5630  
5635  
5640  
5645  
5650  
5655  
5660  
5665  
5670  
5675  
5680  
5685  
5690  
5695  
5700  
5705  
5710  
5715  
5720  
5725  
5730  
5735  
5740  
5745  
5750  
5755  
5760  
5765  
5770  
5775  
5780  
5785  
5790  
5795  
5800  
5805  
5810  
5815  
5820  
5825  
5830  
5835  
5840  
5845  
5850  
5855  
5860  
5865  
5870  
5875  
5880  
5885  
5890  
5895  
5900  
5905  
5910  
5915  
5920  
5925  
5930  
5935  
5940  
5945  
5950  
5955  
5960  
5965  
5970  
5975  
5980  
5985  
5990  
5995  
6000  
6005  
6010  
6015  
6020  
6025  
6030  
6035  
6040  
6045  
6050  
6055  
6060  
6065  
6070  
6075  
6080  
6085  
6090  
6095  
6100  
6105  
6110  
6115  
6120  
6125  
6130  
6135  
6140  
6145  
6150  
6155  
6160  
6165  
6170  
6175  
6180  
6185  
6190  
6195  
6200  
6205  
6210  
6215  
6220  
6225  
6230  
6235  
6240  
6245  
6250  
6255  
6260  
6265  
6270  
6275  
6280  
6285  
6290  
6295  
6300  
6305  
6310  
6315  
6320  
6325  
6330  
6335  
6340  
6345  
6350  
6355  
6360  
6365  
6370  
6375  
6380  
6385  
6390  
6395  
6400  
6405  
6410  
6415  
6420  
6425  
6430  
6435  
6440  
6445  
6450  
6455  
6460  
6465  
6470  
6475  
6480  
6485  
6490  
6495  
6500  
6505  
6510  
6515  
6520  
6525  
6530  
6535  
6540  
6545  
6550  
6555  
6560  
6565  
6570  
6575  
6580  
6585  
6590  
6595  
6600  
6605  
6610  
6615  
6620  
6625  
6630  
6635  
6640  
6645  
6650  
6655  
6660  
6665  
6670  
6675  
6680  
6685  
6690  
6695  
6700  
6705  
6710  
6715  
6720  
6725  
6730  
6735  
6740  
6745  
6750  
6755  
6760  
6765  
6770  
6775  
6780  
6785  
6790  
6795  
6800  
6805  
6810  
6815  
6820  
6825  
6830  
6835  
6840  
6845  
6850  
6855  
6860  
6865  
6870  
6875  
6880  
6885  
6890  
6895  
6900  
6905  
6910  
6915  
6920  
6925  
6930  
6935  
6940  
6945  
6950  
6955  
6960  
6965  
6970  
6975  
6980  
6985  
6990  
6995  
7000  
7005  
7010  
7015  
7020  
7025  
7030  
7035  
7040  
7045  
7050  
7055  
7060  
7065  
7070  
7075  
7080  
7085  
7090  
7095  
7100  
7105  
7110  
7115  
7120  
7125  
7130  
7135  
7140  
7145  
7150  
7155  
7160  
7165  
7170  
7175  
7180  
7185  
7190  
7195  
7200  
7205  
7210  
7215  
7220  
7225  
7230  
7235  
7240  
7245  
7250  
7255  
7260  
7265  
7270  
7275  
7280  
7285  
7290  
7295  
7300  
7305  
7310  
7315  
7320  
7325  
7330  
7335  
7340  
7345  
7350  
7355  
7360  
7365  
7370  
7375  
7380  
7385  
7390  
7395  
7400  
7405  
7410  
7415  
7420  
7425  
7430  
7435  
7440  
7445  
7450  
7455  
7460  
7465  
7470  
7475  
7480  
7485  
7490  
7495  
7500  
7505  
7510  
7515  
7520  
7525  
7530  
7535  
7540  
7545  
7550  
7555  
7560  
7565  
7570  
7575  
7580  
7585  
7590  
7595  
7600  
7605  
7610  
7615  
7620  
7625  
7630  
7635  
7640  
7645  
7650  
7655  
7660  
7665  
7670  
7675  
7680  
7685  
7690  
7695  
7700  
7705  
7710  
7715  
7720  
7725  
7730  
7735  
7740  
7745  
7750  
7755  
7760  
7765  
7770  
7775  
7780  
7785  
7790  
7795  
7800  
7805  
7810  
7815  
7820  
7825  
7830  
7835  
7840  
7845  
7850  
7855  
7860  
7865  
7870  
7875  
7880  
7885  
7890  
7895  
7900  
7905  
7910  
7915  
7920  
7925  
7930  
7935  
7940  
7945  
7950  
7955  
7960  
7965  
7970  
7975  
7980  
7985  
7990  
7995  
8000  
8005  
8010  
8015  
8020  
8025  
8030  
8035  
8040  
8045  
8050  
8055  
8060  
8065  
8070  
8075  
8080  
8085  
8090  
8095  
8100  
8105  
8110  
8115  
8120  
8125  
8130  
8135  
8140  
8145  
8150  
8155  
8160  
8165  
8170  
8175  
8180  
8185  
8190  
8195  
8200  
8205  
8210  
8215  
8220  
8225  
8230  
8235  
8240  
8245  
8250  
8255  
8260  
8265  
8270  
8275  
8280  
8285  
8290  
8295  
8300  
8305  
8310  
8315  
8320  
8325  
8330  
8335  
8340  
8345  
8350  
8355  
8360  
8365  
8370  
8375  
8380  
8385  
8390  
8395  
8400  
8405  
8410  
8415  
8420  
8425  
8430  
8435  
8440  
8445  
8450  
8455  
8460  
8465  
8470  
8475  
8480  
8485  
8490  
8495  
8500  
8505  
8510  
8515  
8520  
8525  
8530  
8535  
8540  
8545  
8550  
8555  
8560  
8565  
8570  
8575  
8580  
8585  
8590  
8595  
8600  
8605  
8610  
8615  
8620  
8625  
8630  
8635  
8640  
8645  
8650  
8655  
8660  
8665  
8670  
8675  
8680  
8685  
8690  
8695  
8700  
8705  
8710  
8715  
8720  
8725  
8730  
8735  
8740  
8745  
8750  
8755  
8760  
8765  
8770  
8775  
8780  
8785  
8790  
8795  
8800  
8805  
8810  
8815  
8820  
8825  
8830  
8835  
8840  
8845  
8850  
8855  
8860  
8865  
8870  
8875  
8880  
8885  
8890  
8895  
8900  
8905  
8910  
8915  
8920  
8925  
8930  
8935  
8940  
8945  
8950  
8955  
8960  
8965  
8970  
8975  
8980  
8985  
8990  
8995  
9000  
9005  
9010  
9015  
9020  
9025  
9030  
9035  
9040  
9045  
9050  
9055  
9060  
9065  
9070  
9075  
9080  
9085  
9090  
9095  
9100  
9105  
9110  
9115  
9120  
9125  
9130  
9135  
9140  
9145  
9150  
9155  
9160  
9165  
9170  
9175  
9180  
9185  
9190  
9195  
9200  
9205  
9210  
9215  
9220  
9225  
9230  
9235  
9240  
9245  
9250  
9255  
9260  
9265  
9270  
9275  
9280  
9285  
9290  
9295  
9300  
9305  
9310  
9315  
9320  
9325  
9330  
9335  
9340  
9345  
9350  
9355  
9360  
9365  
9370  
9375  
9380  
9385  
9390  
9395  
9400  
9405  
9410  
9415  
9420  
9425  
9430  
9435  
9440  
9445  
9450  
9455  
9460  
9465  
9470  
9475  
9480  
9485  
9490  
9495  
9500  
9505  
9510  
9515  
9520  
9525  
9530  
9535  
9540  
9545  
9550  
9555  
9560  
9565  
9570  
9575  
9580  
9585  
9590  
9595  
9600  
9605  
9610  
9615  
9620  
9625  
9630  
9635  
9640  
9645  
9650  
9655  
9660  
9665  
9670  
9675  
9680  
9685  
9690  
9695  
9700  
9705  
9710  
9715  
9720  
9725  
9730  
9735  
9740  
9745  
9750  
9755  
9760  
9765  
9770  
9775  
9780  
9785  
9790  
9795  
9800  
9805  
9810  
9815  
9820  
9825  
9830  
9835  
9840  
9845  
9850  
9855  
9860  
9865  
9870  
9875  
9880  
9885  
9890  
9895  
9900  
9905  
9910  
9915  
9920  
9925  
9930  
9935  
9940  
9945  
9950  
9955  
9960  
9965  
9970  
9975  
9980  
9985  
9990  
9995  
10000  
10005  
10010  
10015  
10020  
10025  
10030  
10035  
10040  
10045  
10050  
10055  
10060  
10065  
10070  
10075  
10080  
10085  
10090  
10095  
10100  
10105  
10110  
10115  
10120  
10125  
10130  
10135  
10140  
10145  
10150  
10155  
10160  
10165  
10170  
10175  
10180  
10185  
10190  
10195  
10200  
10205  
10210  
10215  
10220  
10225  
10230  
10235  
10240  
10245  
10250  
10255  
10260  
10265  
10270  
10275  
10280  
10285  
10290  
10295  
10300  
10305  
10310  
10315  
10320  
10325  
10330  
10335  
10340  
10345  
10350  
10355  
10360  
10365  
10370  
10375  
10380  
10385  
10390  
10395  
10400  
10405  
10410  
10415  
10420  
10425  
10430  
10435  
10440  
10445  
10450  
10455  
10460  
10465  
10470  
10475  
10480  
10485  
10490  
10495  
10500  
10505  
10510  
10515  
10520  
10525  
10530  
10535  
10540  
10545  
10550  
10555  
10560  
10565  
10570  
10575  
10580  
10585  
10590  
10595  
10600  
10605  
10610  
10615  
10620  
10625  
10630  
10635  
10640  
10645  
10650  
10655  
10660  
10665  
10670  
10675  
10680  
10685  
10690  
10695  
10700  
10705  
10710  
10715  
10720  
10725  
10730  
10735  
10740  
10745  
10750  
10755  
10760  
10765  
10770  
10775  
10780  
10785  
10790  
10795  
10800  
10805  
10810  
10815  
10820  
10825  
10830  
10835  
10840  
10845  
10850  
10855  
10860  
10865  
10870  
10875  
10880  
10885  
10890  
10895  
10900  
10905  
10910  
10915  
10920  
10925  
10930  
10935  
10940  
10945  
10950  
10955  
10960  
10965  
10970  
10975  
10980  
10985  
10990  
10995  
11000  
11005  
11010  
11015  
11020  
11025  
11030  
11035  
11040  
11045  
11050  
11055  
11060  
11065  
11070  
11075  
11080  
11085  
11090  
11095  
11100  
11105  
11110  
11115  
11120  
11125  
11130  
11135

PLD  
B/C  
a temperature of about 325 °C and a pressure of about 8 bars absolute the resulting equivalent liquids was  $8.38 \times 10^{-5} \text{ m}^3/\text{kg}$ . As temperature of the retort increased and the pressure decreased the yield of the equivalent liquids produced increased. Equivalent liquids produced was defined as the amount of liquid equivalent to the energy value of the produced gas and liquids.

FIG. 94 illustrates a plot of oil yield produced from treating an oil shale formation, measured as volume of liquids per ton of the formation, as a function of temperature and pressure of the retort. Temperature is illustrated in units of Celsius on the x-axis, and pressure is illustrated in units of bars absolute on the y-axis. As shown in FIG. 94, the yield of liquid/condensable products increases as temperature of the retort increases and pressure of the retort decreases. The lines on FIG. 94 correspond to different liquid production rates measured as the volume of liquids produced per weight of oil shale and are shown in Table 3.

On page 227, please delete the three paragraphs beginning on line 2, and substitute therefor:

PLD  
FIG. 95 illustrates yield of oil produced from treating an oil shale formation expressed as a percent of Fischer assay as a function of temperature and pressure. Temperature is illustrated in units of degrees Celsius on the x-axis, and gauge pressure is illustrated in units of bars on the y-axis. Fischer assay was used as a method for assessing a recovery of hydrocarbon condensate from the oil shale. In this case, a maximum recovery would be 100% of the Fischer assay. As the temperature decreased and the pressure increased, the percent of Fischer assay yield decreased.

FIG. 96 illustrates hydrogen to carbon ratio of hydrocarbon condensate produced from an oil shale formation as a function of a temperature and pressure. Temperature is illustrated in units of degrees Celsius on the x-axis, and pressure is illustrated in units of bars on the y-axis.



As shown in FIG. 96, a hydrogen to carbon ratio of hydrocarbon condensate produced from an oil shale formation decreases as a temperature increases and as a pressure decreases. As described in more detail with respect to other embodiments herein, treating an oil shale formation at high temperatures may decrease a hydrogen concentration of the produced hydrocarbon condensate.

FIG. 97 illustrates the effect of pressure and temperature within an oil shale formation on a ratio of olefins to paraffins. The relationship of the value of one of the properties (R) with temperature has the same functional form as the pressure-temperature relationships previously discussed. In this case the property (R) can be explicitly expressed as a function of pressure and temperature.

$$R = \exp[F(P)/T] + G(P)$$
$$F(p) = f_1 * (P)^3 + f_2 * (P)^2 + f_3 * (P) + f_4$$
$$G(p) = g_1 * (P)^3 + g_2 * (P)^2 + g_3 * (P) + g_4$$

wherein R a value of the property, T is the absolute temperature (in degrees Kelvin),  $F(P)$  and  $G(P)$  are functions of pressure representing the slope and intercept of a plot of R versus  $1/T$ .

On page 228, please delete the two paragraphs beginning on line 23, and substitute therefor:

FIG. 98 illustrates a relationship between an API gravity of a hydrocarbon condensate fluid, the partial pressure of molecular hydrogen within the fluid, and a temperature within an oil shale formation. As illustrated in FIG. 98, as a partial pressure of hydrogen within the fluid increased, the API gravity generally increased. In addition, lower pyrolysis temperatures appear to have increased the API gravity of the produced fluids. Maintaining a partial pressure of

ple 3  
molecular hydrogen within a heated portion of a hydrocarbon containing formation may increase the API gravity of the produced fluids.

In FIG. 99, a quantity of oil liquids produced in m<sup>3</sup> of liquids per kg of oil shale formation is plotted versus a partial pressure of H<sub>2</sub>. Also illustrated in FIG. 99 are various curves for pyrolysis occurring at different temperatures. At higher pyrolysis temperatures production of oil liquids was higher than at the lower pyrolysis temperatures. In addition, high pressures tended to decrease the quantity of oil liquids produced from an oil shale formation. Operating an in situ conversion process at low pressures and high temperatures may produce a higher quantity of oil liquids than operating at low temperatures and high pressures.

On page 229, please delete the paragraph beginning on line 24, and substitute therefor:

As illustrated in FIG. 104, the field experiment consisted of a single unconfined hexagonal seven spot pattern on eight foot spacing. Six heat injection wells 3600, drilled to a depth of 40 m, contained 17 m long heating elements that injected thermal energy into the formation from 21 m to 39 m. A single producer well 3602 in the center of the pattern captured the liquids and vapors from the in-situ retort. Three observation wells 3603 inside the pattern and one outside the pattern recorded formation temperatures and pressures. Six dewatering wells 3604 surrounded the pattern on 6 m spacing and were completed in an active aquifer below the heated interval (from 44 m to 61 m). FIG. 105 is a cross-sectional view of the field experiment. A producer well 3602 includes pump 3614. A lower portion 3612 of producer well 3602 was packed with gravel. An upper portion 3610 of producer well 3602 was cemented. Heater well 3600 was located a distance of approximately 2.4 meters from producer well 3602. A heating element was located within the heater well and the heater well was cemented in place. Dewatering wells 3604 were located approximately 4.0 meters from heater wells 3600. Coring well 3606 was located approximately 0.5 m from heater wells 3600.

On page 230, please delete the paragraph beginning on line 29, and substitute therefor:

Pl65  
FIG. 106 illustrates a plot of the maximum temperatures within each of the three innermost observation wells 3603 (see FIG. 104) versus time. The temperature profiles were very similar for the three observation wells. Heat was provided to the oil shale formation for 216 days. As illustrated in FIG. 106, the temperature at the observer wells increased steadily until the heat was turned off.

On page 231, please delete the paragraph beginning on line 20, and substitute therefor:

Pl66  
FIG. 107  
As illustrated in FIG. 107, pressure within the oil shale material showed some variations initially at different depths, however over time these variations equalized. FIG. 107 depicts the gauge fluid pressure in the observation well 3603 versus time measured in days at a radial distance of 2.1 m from the production well 3602. The fluid pressures were monitored at depths of 24 m and 33 m. These depths corresponded to a richness within the oil shale material of  $8.3 \times 10^{-5} \text{ m}^3$  of oil / kg of oil shale at 24 m and  $1.7 \times 10^{-4} \text{ m}^3$  of oil / kg of oil shale at 33 m. The higher pressures initially observed at 33 m may be the result of a higher generation of fluids due to the richness of the oil shale material at that depth. In addition, at lower depths a lithostatic pressure may be higher, causing the oil shale material at 33 m to fracture at higher pressure than at 24 m. During the course of the experiment, pressures within the oil shale formation equalized. The equalization of the pressure may have resulted from fractures forming within the oil shale formation.

On page 233, please delete the paragraph beginning on line 22, and substitute therefor:

Pl67  
Experimental data from studies conducted by Lawrence Livermore National Laboratories (LLNL) was plotted along with laboratory data from the in situ conversion process (ICP) for an oil shale formation at atmospheric pressure in FIG. 113. The oil recovery as a percent of Fischer

AL67  
assay was plotted against a log of the heating rate. Data from LLNL 3642 included data derived from pyrolyzing powdered oil shale at atmospheric pressure and in a range from about 2 bars absolute to about 2.5 bars absolute. As illustrated in FIG. 113, the data from LLNL 3642 has a linear trend. Data from the ICP 3640 demonstrates that oil recovery, as measured by Fischer assay, was much higher for ICP than the data from LLNL would suggest 3642. FIG. 113 demonstrates that oil recovery from oil shale increases along an S-curve.

---

On page 234, please delete the paragraph beginning on line 14, and substitute therefor:

---

AL68  
FOOTNOTES  
A series of experiments was conducted to determine the effects of various properties of hydrocarbon containing formations on properties of fluids produced from coal formations. The fluids may be produced according to any of the embodiments as described herein. The series of experiments included organic petrography, proximate/ultimate analyses, Rock-Eval pyrolysis, Leco Total Organic Carbon ("TOC"), Fischer Assay, and pyrolysis-gas chromatography. Such a combination of petrographic and chemical techniques may provide a quick and inexpensive method for determining physical and chemical properties of coal and for providing a comprehensive understanding of the effect of geochemical parameters on potential oil and gas production from coal pyrolysis. The series of experiments were conducted on forty-five cubes of coal to determine source rock properties of each coal and to assess potential oil and gas production from each coal.

---

On page 236, please delete the three paragraphs beginning on line 23, and substitute therefor:

---

AL69  
Results were also displayed as a yield of products. FIG. 121-124 illustrate the yields of components in terms of m<sup>3</sup> of product per kg of hydrocarbon containing formation, when measured on a dry, ash free basis. As illustrated in FIG. 121 the yield of paraffins increased as the vitrinite reflectance of the coal increased. However, for coals with a vitrinite reflectance

ALG  
greater than about 0.7 to 0.8% the yield of paraffins fell off dramatically. In addition, a yield of cycloalkanes followed similar trends as the paraffins, increasing as the vitrinite reflectance of coal increased and decreasing for coals with a vitrinite reflectance greater than about 0.7% or 0.8% as illustrated in FIG. 122. FIG. 123 illustrates the increase of both paraffins and cycloalkanes as the vitrinite reflectance of coal increases to about 0.7% or 0.8%. As illustrated in FIG. 124, the yield of phenols may be relatively low for coal material with a vitrinite reflectance of less than about 0.3% and greater than about 1.25%. Production of phenols may be desired due to the value of phenol as a feedstock for chemical synthesis.

As demonstrated in FIG. 125, the API gravity appears to increase significantly when the vitrinite reflectance is greater than about 0.4%. FIG. 126 illustrates the relationship between coal rank, (i.e., vitrinite reflectance), and a yield of condensable hydrocarbons (in gallons per ton on a dry ash free basis) from a coal formation. The yield in this experiment appears to be in an optimal range when the coal has a vitrinite reflectance greater than about 0.4% to less than about 1.3%.

FIG. 127 illustrates a plot of CO<sub>2</sub> yield of coal having various vitrinite reflectances. In FIGS. 127 and 128, CO<sub>2</sub> yield is set forth in weight percent on a dry ash free basis. As shown in FIG. 127, at least some CO<sub>2</sub> was released from all of the coal samples. Such CO<sub>2</sub> production may correspond to various oxygenated functional groups present in the initial coal samples. A yield of CO<sub>2</sub> produced from low-rank coal samples was significantly higher than a production from high-rank coal samples. Low-rank coals may include lignite and sub-bituminous brown coals. High-rank coals may include semi-anthracite and anthracite coal. FIG. 128 illustrates a plot of CO<sub>2</sub> yield from a portion of a coal formation versus the atomic O/C ratio within a portion of a coal formation. As O/C atomic ratio increases, a CO<sub>2</sub> yield increases.

On page 241, please delete the paragraph beginning on line 14, and substitute therefor:

A70

As shown in FIG. 131, methane started to be produced at temperatures at or above about 270 °C. Since the experiments were conducted at atmospheric pressure, it is believed that the methane is produced from the pyrolysis, and not from mere desorption. Between about 270 °C and about 400 °C, condensable hydrocarbons, methane and H<sub>2</sub> were produced as shown in FIGS. 131, 132, and 133. FIG. 131 shows that above a temperature of about 400 °C methane and H<sub>2</sub> continue to be produced. Above about 450 °C, however, methane concentration decreased in the produced gases whereas the produced gases contained increased amounts of H<sub>2</sub>. If heating were continued, eventually all H<sub>2</sub> remaining in the coal would be depleted, and production of gas from the coal would cease. FIGS. 131-133 indicate that the ratio of a yield of gas to a yield of condensable hydrocarbons will increase as the temperature increases above about 390°C.

On page 242, please delete the paragraph beginning on line 5, and substitute therefor:

A71

An experiment was conducted to determine an effect of heating on thermal conductivity and thermal diffusivity of a portion of a coal formation. Thermal pulse tests performed in situ in a high volatile bituminous C coal at the field pilot site showed a thermal conductivity between  $2.0 \times 10^{-3}$  to  $2.39 \times 10^{-3}$  cal/cm sec °C (0.85 to 1.0 W/(m °K)) at 20 °C. Ranges in these values were due to different measurements between different wells. The thermal diffusivity was  $4.8 \times 10^{-3}$  cm<sup>2</sup>/s at 20 °C (the range was from about  $4.1 \times 10^{-3}$  to about  $5.7 \times 10^{-3}$  cm<sup>2</sup>/s at 20 °C). It is believed that these measured values for thermal conductivity and thermal diffusivity are substantially higher than would be expected based on literature sources (e.g., about three times higher in many instances).

On page 244, please delete the two paragraphs beginning on line 10, and substitute therefor:

A72  
B20

~~Hydrocarbon fluids were produced from a portion of a coal formation by an in situ~~  
experiment conducted in a portion of a coal formation. The coal was high volatile bituminous C coal. It was heated with electrical heaters. FIG. 136 illustrates a cross-sectional view of the in situ experimental field test system. As shown in FIG. 136, the experimental field test system included at least coal formation 3802 within the ground and grout wall 3800. Coal formation 3802 dipped at an angle of approximately 36° with a thickness of approximately 4.9 meters. FIG. 137 illustrates a location of heat sources 3804a, 3804b, 3804c, production wells 3806a, 3806b, and temperature observation wells 3808a, 3808b, 3808c, 3808d used for the experimental field test system. The three heat sources were disposed in a triangular configuration. Production well 3806a was located proximate a center of the heat source pattern and equidistant from each of the heat sources. A second production well 3806b was located outside the heat source pattern and spaced equidistant from the two closest heat sources. Grout wall 3800 was formed around the heat source pattern and the production wells. The grout wall may include pillars 1-24. Grout wall 3800 was configured to inhibit an influx of water into the portion during the in situ experiment. In addition, grout wall 3800 was configured to substantially inhibit loss of generated hydrocarbon fluids to an unheated portion of the formation.

TEMPERATURE OBSERVATION WELLS

Temperatures were measured at various times during the experiment at each of four temperature observation wells 3808a, 3808b, 3808c, 3808d located within and outside of the heat source pattern as illustrated in FIG. 137. The temperatures measured (in degrees Celsius) at each of the temperature observation wells are displayed in FIG. 138 as a function of time. Temperatures at observation wells 3808a (3820), 3808b (3822), and 3808c (3824) were relatively close to each other. A temperature at temperature observation well 3808d (3826) was significantly colder. This temperature observation well was located outside of the heater well triangle illustrated in FIG. 137. This data demonstrates that in zones where there was little superposition of heat, temperatures were significantly lower. FIG. 139 illustrates temperature

A72

profiles measured at the heat sources 3804a (3830), 3804b (3832), and 3804c (3834). The temperature profiles were relatively uniform at the heat sources.

On page 245, please delete the paragraph beginning on line 23, and substitute therefor:

A73

Table 5 illustrates the results from analyzing coal before and after it was treated (including heating to the temperatures as set forth in FIG. 139 (i.e., after pyrolysis and production of synthesis gas)) as described above. The coal was cored at about 11-11.3 meters from the surface, midway into the coal bed, in both the "before treatment" and "after treatment" examples. Both cores were taken at about the same location. Both cores were taken at about 0.66 meters from well 3804c (between the grout wall and well 3804c) in FIG. 137. In the following Table 5 "FA" means Fisher Assay, "as rec'd" means the sample was tested as it was received and without any further treatment, "Py-Water" means the water produced during pyrolysis, "H/C Atomic Ratio" means the atomic ratio of hydrogen to carbon, "daf" means "dry ash free," "dmmf" means "dry mineral matter free," and "mmf" means "mineral matter free." The specific gravity of the "after treatment" core sample was approximately 0.85 whereas the specific gravity of the "before treatment" core sample was approximately 1.35.

103007-2214500

On page 247, please delete the paragraph beginning on line 19, and substitute therefor:

A74

FIG. 143 illustrates a bar graph of fractions from a boiling point separation of hydrocarbon liquids generated by a Fischer assay and a boiling point separation of hydrocarbon liquids from the coal cube experiment described herein (see, e.g., the system shown in FIG. 129). The experiment was conducted at a much slower heating rate (2 degrees Celsius per day) and the oil produced at a lower final temperature than the Fischer Assay. FIG. 143 shows the weight percent of various boiling point cuts of hydrocarbon liquids produced from a Fruitland high volatile bituminous B coal. Different boiling point cuts may represent different hydrocarbon fluid compositions. The boiling point cuts illustrated include naphtha 3860 (initial boiling point



A74  
to 166°C), jet fuel 3862 (166°C to 249°C), diesel 3864 (249°C to 370°C), and bottoms 3866 (boiling point greater than 370°C). The hydrocarbon liquids from the coal cube were substantially more valuable products. The API gravity of such hydrocarbon liquids was significantly greater than the API gravity of the Fischer Assay liquid. The hydrocarbon liquids from the coal cube also included significantly less residual bottoms than were produced from the Fischer Assay hydrocarbon liquids.

On page 248, please delete the paragraph beginning on line 28, and substitute therefor:

A75  
The system depicted in FIG. 89, and the method of using such system (see other discussion herein with respect to using such system to conduct oil shale experiments) was used to conduct experiments on high volatile bituminous C coal when such coal was heated at 5 °C/day at atmospheric pressure. FIG. 103 depicts certain data points from such experiment (the line depicted in FIG. 103 was produced from a linear regression analysis of such data points). FIG. 103 illustrates the ethene to ethane molar ratio as a function of hydrogen molar concentration in non-condensable hydrocarbons produced from the coal during the experiment. The ethene to ethane ratio in the non-condensable hydrocarbons is reflective of olefin content in all hydrocarbons produced from the coal. As can be seen in FIG. 103, as the concentration of hydrogen autogenously increased during pyrolysis, the ratio of ethene to ethane decreased. It is believed that increases in the concentration (and partial pressure) of hydrogen during pyrolysis causes the olefin concentration to decrease in the fluids produced from pyrolysis.

On page 249, please delete the two paragraphs beginning on line 20, and substitute therefor:

A76  
FIG. 146 illustrates weight percentages of various carbon numbers products removed from high volatile bituminous "C" coal when coal is heated at various heating rates. Data points were derived from laboratory experiments and a Fischer assay. Curves for heating at a rate of 2

A74  
°C/day 3870, 3 °C/day 3872, 5 °C/day 3874, and 10 °C/day 3876 provided for similar carbon number distributions in the produced fluids. A coal sample was also heated in a Fischer assay test at a rate of about 17,100 °C/day. The data from the Fischer assay test is indicated by reference numeral 3878. Slow heating rates resulted in less production of components having carbon numbers greater than 20 as compared to the Fischer assay results 3878. Lower heating rates also produced higher weight percentages of components with carbon numbers less than 20. The lower heating rates produced large amounts of components having carbon numbers near 12. A peak in carbon number distribution near 12 is typical of the in situ conversion process for coal and oil shale.

FIG. 137  
An experiment was conducted on the coal formation treated according to the in situ conversion process to measure the uniform permeability of the formation after pyrolysis. After heating a portion of the coal formation, a ten minute pulse of CO<sub>2</sub> was injected into the formation at first production well 3806a and produced at well 3804a, as shown in FIG. 137. The CO<sub>2</sub> tracer test was repeated from production well 3806a to well 3804b and from production well 3806a to well 3804c. As described above, each of the three different heat sources were located equidistant from the production well. The CO<sub>2</sub> was injected at a rate of 4.08 m<sup>3</sup>/hr (144 standard cubic feet per hour). As illustrated in FIG. 147, the CO<sub>2</sub> reached each of the three different heat sources at approximately the same time. Line 3900 illustrates production of CO<sub>2</sub> at heat source 3804a, line 3902 illustrates production of CO<sub>2</sub> at heat source 3804b, and line 3904 illustrates production of CO<sub>2</sub> at heat source 3804c. As shown in FIG. 149, yield of CO<sub>2</sub> from each of the three different wells was also approximately equal over time. Such approximately equivalent transfer of a tracer pulse of CO<sub>2</sub> through the formation and yield of CO<sub>2</sub> from the formation indicated that the formation was substantially uniformly permeable. The fact that the first CO<sub>2</sub> arrival only occurs approximately 18 minutes after start of the CO<sub>2</sub> pulse indicates that no preferential paths had been created between well 3806a and 3804a, 3804b, and 3804c.

On page 250, please delete the paragraph beginning on line 26, and substitute therefor:

A77  
Synthesis gas was also produced in an in situ experiment from the portion of the coal formation shown in FIG. 136 and FIG. 137. In this experiment, heater wells were also configured to inject fluids. FIG. 148 is a plot of weight of produced volatiles (oil and noncondensable gas) in kilograms as a function of cumulative energy input in kilowatt hours with regard to the in situ experimental field test. The figure illustrates the quantity and energy content of pyrolysis fluids and synthesis gas produced from the formation.

On page 252, please delete the paragraph beginning on line 4, and substitute therefor:

A78  
FIG. 152 illustrates production rate of synthesis gas ( $\text{m}^3/\text{min}$ ) as a function of steam injection rate ( $\text{kg/h}$ ) in a coal formation. Data 3930 for a first run corresponds to injection at producer well 3806a in FIG. 137, and production of synthesis gas at heater wells 3804a, 3804b, and 3804c. Data 3932 for a second run corresponds to injection of steam at heater well 3804c, and production of additional gas at a production well 3806a. Data 3930 for the first run corresponds to the data shown in FIG. 151. As shown in FIG. 152, the injected water is in reaction equilibrium with the formation to about 2.7  $\text{kg/h}$  of injected water. The second run results in substantially the same amount of additional synthesis gas produced, shown by data 3932, as the first run to about 1.2  $\text{kg/h}$  of injected steam. At about 1.2  $\text{kg/h}$ , data 3930 starts to deviate from equilibrium conditions because the residence time is insufficient for the additional water to react with the coal. As temperature is increased, a greater amount of additional synthesis gas is produced for a given injected water rate. The reason is that at higher temperatures the reaction rate and conversion of water into synthesis gas increases.

On page 253, please delete the paragraph beginning on line 14, and substitute therefor:

A79  
FIG. 155 is a plot that illustrates the effect of propane injection into a heated coal

A79  
formation in the experimental field test. Propane was injected into production wells 3806a and 3806b and fluid was produced from heater wells 3804a, 3804b, and 3804c. The average temperatures measured at various wells were as follows: 3804a (737 °C), 3804b (753 °C), 3804c (726 °C), 3808a (589 °C), 3808b (573 °C), 3808c (606 °C), and 3806a (769 °C). When propane contacted the formation, it cracked to produce H<sub>2</sub>, methane, ethane, ethene, propylene and coke. FIG. 155 shows that as the propane injection rate increased, the production of H<sub>2</sub> 3960, methane 3962, ethane 3964, ethene 3966, propane 3968, and propylene 3969 increased. This indicates that propane is cracking to form H<sub>2</sub> and lower molecular weight components.

On page 256, please delete the paragraph beginning on line 4, and substitute therefor:

A80  
B24  
FIG. 160 is a plot of calculated equilibrium wet mole fractions for a coal reaction with water. Equilibrium wet mole fractions are shown for water 4006, H<sub>2</sub> 4008, carbon monoxide 4010, and carbon dioxide 4012 as a function of temperature at a pressure of 2 bar absolute. At 390 °C, the produced gas includes about 89 % water, about 7 % H<sub>2</sub>, and about 4 % carbon dioxide. At 500 °C, the produced gas includes about 66 % water, about 22 % H<sub>2</sub>, about 11 % carbon dioxide, and about 1 % carbon monoxide. At 700 °C, the produced gas includes about percent 18 % water, about 47.5 % H<sub>2</sub>, about 12 % carbon dioxide, and about 22.5 % carbon monoxide.

On page 257, please delete the three paragraphs beginning on line 11, and substitute therefor:

A81  
B25  
In the embodiments in FIGS. 162-164 the methane reactions in Equations (4) and (5) are included. The calculations set forth herein assume that char is only made of carbon and that there is an excess of carbon to steam. About 890 MW of energy 4024 is required to pyrolyze about 105,800 metric tons per day of coal. The pyrolysis products 4028 include liquids and gases with a production of 23,000 cubic meters per day. The pyrolysis process also produces

A31  
B25  
~~about 7,160 metric tons per day of water 4030. In the synthesis gas stage about 57,800 metric tons per day of char with injection of 23,000 metric tons per day of steam 4032 and 2,000 MW of energy 4034 with a 20% conversion will produce 12,700 cubic meters equivalent oil per day of synthesis gas 4038.~~

FIG. 162 is an example of a low temperature in situ synthesis gas production that occurs at a temperature of about 450 °C with heat and mass balances in a hydrocarbon containing formation that was previously pyrolyzed. A total of about 42,900 metric tons per day of water is injected into formation 4100 which may be char. FIG. 162 illustrates that a portion of water 4102 at 25 °C is injected directly into the formation 4100. A portion of water 4102 is converted into steam 4104 at a temperature of about 130 °C and a pressure at about 3 bars absolute using about 1227 MW of energy 4106 and injected into formation 4100. A portion of the remaining steam may be converted into steam 4108 at a temperature of about 450 °C and a pressure at about 3 bars absolute using about 318 MW of energy 4110. The synthesis gas production involves about 23% conversion of 13,137 metric tons per day of char to produce 56.6 millions of cubic meters per day of synthesis gas with an energy content of 5,230 MW. About 238 MW of energy 4112 is supplied to formation 4100 to account for the endothermic heat of reaction of the synthesis gas reaction. The product stream 4114 of the synthesis gas reaction includes 29,470 metric tons per day of water at 46 volume percent, 501 metric tons per day carbon monoxide at 0.7 volume percent, 540 tons per day H<sub>2</sub> at 10.7 volume percent, 26,455 metric tons per day carbon dioxide at 23.8 volume percent, and 7,610 metric tons per day methane at 18.8 volume percent.

FIG. 163 is an example of a high temperature in situ synthesis gas production that occurs at a temperature of about 650 °C with heat and mass balances in a hydrocarbon containing formation that was previously pyrolyzed. A total of about 34,352 metric tons per day of water is

A71  
injected into formation 4200. FIG. 163 illustrates that a portion of water 4202 at 25 °C is injected directly into formation 4200. A portion of water 4202 is converted into steam 4204 at a temperature of about 130 °C and a pressure at about 3 bars absolute using about 982 MW of energy 4206, and injected into formation 4200. A portion of the remaining steam is converted into steam 4208 at a temperature of about 650 °C and a pressure at about 3 bars absolute using about 413 MW of energy 4210. The synthesis gas production involves about 22% conversion of 12,771 metric tons per day of char to produce 56.6 millions of cubic meters per day of synthesis gas with an energy content of 5,699 MW. About 898 MW of energy 4212 is supplied to formation 4200 to account for the endothermic heat of reaction of the synthesis gas reaction. The product stream 4214 of the synthesis gas reaction includes 10,413 metric tons per day of water at 22.8 volume percent, 9,988 metric tons per day carbon monoxide at 14.1 volume percent, 1771 metric tons per day H<sub>2</sub> at 35 volume percent, 21,410 metric tons per day carbon dioxide at 19.3 volume percent, and 3535 metric tons per day methane at 8.7 volume percent.

On page 265, please delete the paragraph beginning on line 28, and substitute therefor:

A82  
FIG. 166 is a flowchart of an embodiment of an in situ synthesis gas production process 4510 integrated with a SMDS Fischer-Tropsch and wax cracking process with heat and mass balances. The synthesis gas generating fluid injected into the formation includes about 24,000 metric tons per day of water 4530, which includes about 5,500 metric tons per day of water 4540 recycled from the SMDS Fischer-Tropsch and wax cracking process 4520. A total of about 1700 MW of energy is supplied to the in situ synthesis gas production process 4510. About 1020 MW of energy 4535 of the approximately 1700 MW of energy is supplied by in situ reaction of an oxidizing fluid with the formation, and approximately 680 MW of energy 4550 is supplied by the SMDS Fischer-Tropsch and wax cracking process 4520 in the form of steam. About 12,700 cubic meters equivalent oil per day of synthesis gas 4560 is used as feed gas to the SMDS Fischer-Tropsch and wax cracking process 4520. The SMDS Fischer-Tropsch and wax cracking

A22  
process 4520 produces about 4,770 cubic meters per day of products 4570 that may include naphtha, kerosene, diesel, and about 5,880 cubic meters equivalent oil per day of off gas 4580 for a power generation facility.

On page 266, please delete the paragraph beginning on line 22, and substitute therefor:

A23  
The simulation of H<sub>2</sub> 4604 provides a good fit to observed fraction of H<sub>2</sub> 4603. The simulation of methane 4602 provides a good fit to observed fraction of methane 4601. The simulation of carbon dioxide 4606 provides a good fit to observed fraction of carbon dioxide 4605. The simulation of CO 4608 overestimated the fraction of CO 4607 by 4-5 percentage points. Carbon monoxide is the most difficult of the synthesis gas components to model. Also, the carbon monoxide discrepancy may be due to fact that the pattern temperatures exceeded 550 °C, the upper limit at which the numerical model was calibrated.

On page 269, please delete the paragraph beginning on line 1, and substitute therefor:

A24  
As illustrated in Table 9, pyrolysis of the tar sand decreases nitrogen and sulfur weight percentages in a produced fluid and increases carbon weight percentage in a produced fluid. Increasing the pressure in the pyrolysis experiment appears to further decrease the nitrogen and sulfur weight percentage in the produced fluids.

On page 270, please delete the three paragraphs beginning on line 8, and substitute therefor:

A25  
FIG. 168 illustrates plots of weight percentages of carbon compounds versus carbon number for initial tar 4703 and runs at pressures of 1 bar absolute 4704, 7.9 bars absolute 4705, and 28.6 bars absolute 4706 with a heating rate of 10 °C/day. From the plots of initial tar 4703 and a pressure of 1 bar absolute 4704 it can be seen that pyrolysis shifts an average carbon number distribution to relatively lower carbon numbers. For example, a mean carbon number in

the carbon distribution of plot 4703 is at about carbon number nineteen and a mean carbon number in the carbon distribution of plot 4704 is at about carbon number seventeen. Increasing the pressure to 7.9 bars absolute 4705 further shifts the average carbon number distribution to even lower carbon numbers. Increasing the pressure to 7.9 bars absolute 4705 also shifts the mean carbon number in the carbon distribution to a carbon number of about thirteen. Further increasing the pressure to 28.6 bars absolute 4706 reduces the mean carbon number to about eleven. Increasing the pressure is believed to decrease the average carbon number distribution by increasing a hydrogen partial pressure in the product fluid. The increased hydrogen partial pressure in the product fluid allows hydrogenation, dearomatization, and/or pyrolysis of large molecules to form smaller molecules. Increasing the pressure also increases a quality of the produced fluid. For example, the API gravity of the fluid increased from less than about 10° for the initial tar, to about 31° for a pressure of 1 bar absolute, to about 39° for a pressure of 7.9 bars absolute, to about 45° for a pressure of 28.6 bars absolute.

FIG. 169 illustrates bar graphs of weight percentages of carbon compounds for various pyrolysis heating rates and pressures. Bar graph 4710 illustrates weight percentages for pyrolysis with a heating rate of 1 °C/day at a pressure of 1 bar absolute. Bar graph 4712 illustrates weight percentages for pyrolysis with a heating rate of 5 °C/day at a pressure of 1 bar absolute. Bar graph 4714 illustrates weight percentages for pyrolysis with a heating rate of 10 °C/day at a pressure of 1 bar absolute. Bar graph 4716 illustrates weight percentages for pyrolysis with a heating rate of 10 °C/day at a pressure of 7.9 bars absolute. Weight percentages of paraffins 4720, cycloalkanes 4722, mono-aromatics 4724, di-aromatics 4726, and tri-aromatics 4728 are illustrated in the bar graphs. The bar graphs demonstrate that a variation in the heating rate between 1 °C/day to 10 °C/day does not significantly affect the composition of the product fluid. Increasing the pressure from 1 bar absolute to 7.9 bars absolute, however, affects a composition of the product fluid. Such an effect may be characteristic of the effects described in FIG. 168